



Safety Data Sheet dated 6/3/2023, version 1

SECTION 1: Identification of the sub	ostance/mixture and of the company/undertaking
1.1. Product identifier	
Mixture identification:	
Trade name:	ZINCANTE SCURO SPRAY
Trade code:	70.0070
UFI:	1FRH-G04V-D20M-N2N2
1.2. Relevant identified uses of the	substance or mixture and uses advised against
1.3. Details of the supplier of the sa	fety data sheet
Company:	
ARECO ITALIA SPA Via Alfo	nso Capecelatro, 55 20148 Milano
Centro Antiveleni - Ospedale	di Niguarda - Milano - Tel. 0039 02 66101029
Competent person responsible for t	he safety data sheet:
commerciale@arecoitalia.it	
1.4. Emergency telephone number	
Centro Antiveleni - Ospedale	di Niguarda - Milano - Tel. 0039 02 66101029

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
- EC regulation criteria 1272/2008 (CLP):

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

- Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, Eye Irrit. 2, Causes serious eye irritation.
- Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects: No other hazards 2.2. Label elements Hazard pictograms:

70.0070/1 Page n. 1 of 12





Danger

Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P391 Collect spillage.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

acetone; propan-2-one; propanone

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135 oC to 210 oC (275oF to 410oF).]

Special provisions according to Annex XVII of REACH and subsequent amendments: Restricted to professional users.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

- 3.1. Substances
 - N.A.
- 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Nur		Classification
>= 25% -	acetone;	Index	606-001-00-8	📀 2.6/2 Flam. Liq. 2 H225
< 30%	propan-2-one;	number:		



>= 15% - < 20%	propanone propane	Index number: CAS: EC:	67-64-1 200-662-2 01-21194713 30-49 601-003-00-5 74-98-6 200-827-9	 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336 EUH066 2.2/1 Flam. Gas 1 H220 2.5/L Press Gas (Liq.) H280
>= 12.5% -	xylene	REACH No.: Index number:	01-21194869 44-21 601-022-00-9	2.6/3 Flam. Liq. 3 H226
< 15%		CAS: EC:	1330-20-7 215-535-7 01-21194882 16-32	 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332 3.2/2 Skin Irrit. 2 H315
>= 7% - < 10%	butane	Index number: CAS: EC: REACH No.:	601-004-00-0 106-97-8 203-448-7 01-21194746 91-32	 ♦ 2.2/1 Flam. Gas 1 H220 ♦ 2.5/L Press Gas (Liq.) H280
>= 5% - < 7%	and isobutane	Index number: CAS: EC: REACH No.:	601-004-00-0 75-28-5 200-857-2 01-21194853 95-27	 ♦ 2.2/1 Flam. Gas 1 H220 ♦ 2.5/L Press Gas (Liq.) H280
>= 2.5% - < 5%	dimethyl carbonate	Index number: CAS: EC: REACH No.:	607-013-00-6 616-38-6 210-478-4 01-21195483 99-23	🚸 2.6/2 Flam. Liq. 2 H225
>= 2.5% - < 5%	zinc powder - zinc dust (stabilized)		030-002-00-7 7440-66-6 231-175-3 01-21194671 74-37	 4.1/A1 Aquatic Acute 1 H400 4.1/C1 Aquatic Chronic 1 H410
>= 1% - < 2.5%	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of	Index number: CAS: EC: REACH No.:	649-356-00-4 64742-95-6 265-199-0 01-21194558 51-35	 2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H335 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411 EUH066



aromatic hydrocarbons	
having carbon	
numbers	
predominantly in the	
range of C8 through	
C10 and boiling in the	
range of approximately	
135 oC to 210 oC	
(275oF to 410oF).]	

SECTION 4: First aid measures

4.1. Description of first aid measures

- In case of skin contact:
 - Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

- Protect uninjured eye.
- In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed
- None
- 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

- Treatment: None
- None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- CO2 or Dry chemical fire extinguisher.
- Extinguishing media which must not be used for safety reasons:
- None in particular.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.



SECTION 6: Accidental release measures

 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove all sources of ignition. Remove persons to safety.

See protective measures under point 7 and 8.

- 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
- Wash with plenty of water. 6.4. Reference to other sections See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
- Avoid contact with skin and eyes, inhalation of vapours and mists.
 Don't use empty container before they have been cleaned.
 Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 See also section 8 for recommended protective equipment.
 Advice on general occupational hygiene:
 Contamined clothing should be changed before entering eating areas.
 Do not eat or drink while working.
 7.2. Conditions for safe storage, including any incompatibilities
 - Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
 - Keep away from food, drink and feed.
 - Incompatible materials:
 - None in particular.
 - Instructions as regards storage premises:
 - Cool and adequately ventilated.
- 7.3. Specific end use(s) None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters acetone; propan-2-one; propanone - CAS: 67-64-1 EU - TWA(8h): 1210 mg/m3, 500 ppm ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm - Notes: A4, BEI - URT and eye irr, CNS impair propane - CAS: 74-98-6 ACGIH - Notes: (D, EX) - Asphyxia VLE short - 1000 ppm xylene - CAS: 1330-20-7 EU - TWA(8h): 221 mg/m3, 50 ppm - STEL: 442 mg/m3, 100 ppm - Notes: Skin



ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair butane - CAS: 106-97-8 ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair and isobutane - CAS: 75-28-5 ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair VLE short - 1000 ppm **DNEL Exposure Limit Values** N.A. **PNEC Exposure Limit Values** N.A. 8.2. Exposure controls Eye protection: Use close fitting safety goggles, don't use eye lens. Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection: Use adequate protective respiratory equipment. Thermal Hazards: None Environmental exposure controls: None Appropriate engineering controls: None

SECTION 9: Physical and chemical properties

9.1. Information on basic ph Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	N.A.		
Odour:	Caracteristic of solvent		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point:	Inf. 0 ° C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	N.A.		
Kinematic viscosity:	N.A.		
Solubility in water:	N0		
Solubility in oil:	SI		

70.0070/1 Page n. 6 of 12



Partition coefficient	N.A.		
n-octanol/water (log value):			
Vapour pressure:	a 20°C - 4,0		
	bar a		
	50°C - 8,0 bar		
Density and/or relative	0,75 - 0,80		
density:	g/ml		
Relative vapour density:	> of air.		
Particle characteristics:			
Particle size:	N.A.		

9.2. Other information

Properties	Value	Method:	Notes:
Explosive properties:	N.A.		
Oxidizing properties:	N.A.		

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability Stable under normal conditions
- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid Stable under normal conditions.
- 10.5. Incompatible materials Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product:

- ZINCANTE SCURO SPRAY
- a) acute toxicity
 - Not classified
 - Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
 - The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation
 - The product is classified: Eye Irrit. 2 H319
- d) respiratory or skin sensitisation
 - Not classified
 - Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
 - Not classified
 - Based on available data, the classification criteria are not met
- f) carcinogenicity
 - Not classified Based on available data, the classification criteria are not met



```
g) reproductive toxicity
            Not classified
            Based on available data, the classification criteria are not met
      h) STOT-single exposure
            The product is classified: STOT SE 3 H336
      i) STOT-repeated exposure
            Not classified
            Based on available data, the classification criteria are not met
      j) aspiration hazard
            Not classified
            Based on available data, the classification criteria are not met
Toxicological information of the main substances found in the product:
      Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex
      combination of hydrocarbons obtained from distillation of aromatic streams. It consists
      predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range
      of C8 through C10 and boiling in the range of approximately 135 oC to 210 oC (275oF to
      410oF).] - CAS: 64742-95-6
      a) acute toxicity:
            Test: LD50 - Route: Oral - Species: Rat > 6800 mg/kg
            Test: LD50 - Route: Skin - Species: Rabbit > 3400 mg/kg
      acetone; propan-2-one; propanone - CAS: 67-64-1
            LD50 (RABBIT) ORAL: 5300 MG/KG
      xylene - CAS: 1330-20-7
            LD50 (RAT) ORAL: 5000 MG/KG
```

11.2. Information on other hazards Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. ZINCANTE SCURO SPRAY The product is classified: Aquatic Chronic 2 - H411 zinc powder - zinc dust (stabilized) - CAS: 7440-66-6 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Daphnia = 0.44 mg/l - Duration h: 96 12.2. Persistence and degradability None N.A. 12.3. Bioaccumulative potential N.A. 12.4. Mobility in soil N.A. 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None 12.6. Endocrine disrupting properties No endocrine disruptor substances present in concentration >= 0.1% 12.7. Other adverse effects None

70.0070/1 Page n. 8 of 12



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number	
ADR-UN number:	1950
IATA-Un number:	1950
IMDG-Un number:	1950
14.2. UN proper shipping name	
ADR-Shipping Name:	AEROSOL
IATA-Shipping Name:	AEROSOL
IMDG-Shipping Name:	AEROSOL
14.3. Transport hazard class(es)	
ADR-Class:	2 5F
IATA-Class:	2.1
IATA-Label:	2.1
IMDG-Class:	2
14.4. Packing group	
ADR-Packing Group:	-
IATA-Packing group:	-
IMDG-Packing group:	-
14.5. Environmental hazards	
Marine pollutant:	Marine pollutant
IMDG-EMS:	F-D, SU
14.6. Special precautions for user	
IATA-Passenger Aircraft:	
IATA-Cargo Aircraft:	203
IMDG-Shipping Name:	AEROSOL
14.7. Maritime transport in bulk accor	ding to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 2020/878 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP)



Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP) Regulation (EU) n. 2022/692 (ATP 18 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: **Restriction 3 Restriction 40** Restrictions related to the substances contained: **Restriction 28** Restriction 29 **Restriction 75** Volatile Organic compounds - VOCs = 554.40 g/l Volatile CMR substances = 0.00 % Halogenated VOCs which are assigned the risk phrase R40 = 0.00 % Organic Carbon - C = 0.00 Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)

- Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a, E2
- 15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3: H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking. H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H335 May cause respiratory irritation. H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Haza	rd class and	Code	Description
------	--------------	------	-------------



hazard category		
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press Gas (Liq.)	2.5/L	Gases under pressure (Liquefied gas)
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical
	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS: GefStoffVO:	European Inventory of Existing Commercial Chemical Substances. Ordinance on Hazardous Substances, Germany.

70.0070/1 Page n. 11 of 12



GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Áviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.