

**Safety Data Sheet**  
**VERNICE PER CALORIFERI SPRAY**



**Safety Data Sheet dated 21/12/2022, version 1**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Mixture identification:

Trade name: VERNICE PER CALORIFERI SPRAY

Trade code: 91.001

UFI: 5WW3-33JP-W000-56W8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Spray painting decorative household, industrial and professional

1.3. Details of the supplier of the safety data sheet

Company:

ARECO ITALIA SPA Via Foro Bonaparte 70 – 20121 Milano MI

Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. 02 66101029

Competent person responsible for the safety data sheet:

commerciale@arecoitalia.it

1.4. Emergency telephone number


Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. 0039 02 66101029


---


**SECTION 2: Hazards identification**


2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

Hazard pictograms:



Danger

Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read carefully and follow all instructions.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P271 Use only outdoors or in a well-ventilated area.  
 P405 Store locked up.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.  
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

acetone; propan-2-one; propanone

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$

Other Hazards:

No other hazards





## SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.











3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 25\%$ - $< 30\%$	acetone; propan-2-one; propanone	Index number: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 REACH No.: 01-21194713 30-49	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336 EUH066
$\geq 15\%$ - $< 20\%$	propane	Index number: 601-003-00-5	 2.2/1 Flam. Gas 1 H220

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

		CAS: 74-98-6 EC: 200-827-9 REACH No.: 01-21194869 44-21	 2.5/L Press Gas (Liq.) H280
>= 15% - < 20%	xylene	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-21194882 16-32	 2.6/3 Flam. Liq. 3 H226  3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332  3.2/2 Skin Irrit. 2 H315
>= 7% - < 10%	butane	Index number: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 REACH No.: 01-21194746 91-32	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280
>= 5% - < 7%	and isobutane	Index number: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2 REACH No.: 01-21194853 95-27	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280
>= 1% - < 2.5%	dimethyl carbonate	Index number: 607-013-00-6 CAS: 616-38-6 EC: 210-478-4 REACH No.: 01-21195483 99-23	 2.6/2 Flam. Liq. 2 H225

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

#### SECTION 5: Firefighting measures

- 5.1. Extinguishing media
  - Suitable extinguishing media:  
CO2 or Dry chemical fire extinguisher.
  - Extinguishing media which must not be used for safety reasons:  
None in particular.
- 5.2. Special hazards arising from the substance or mixture
  - Do not inhale explosion and combustion gases.
  - Burning produces heavy smoke.
- 5.3. Advice for firefighters
  - Use suitable breathing apparatus .
  - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
  - Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
  - Wear personal protection equipment.
  - Remove all sources of ignition.
  - Remove persons to safety.
  - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
  - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
  - Retain contaminated washing water and dispose it.
  - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
  - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections
  - See also section 8 and 13

---

#### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
  - Avoid contact with skin and eyes, inhalation of vapours and mists.
  - Don't use empty container before they have been cleaned.
  - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
  - See also section 8 for recommended protective equipment.
  - Advice on general occupational hygiene:  
Contaminated clothing should be changed before entering eating areas.
  - Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
  - Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
  - Keep away from food, drink and feed.

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

---

## SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone; propan-2-one; propanone - CAS: 67-64-1

EU - TWA(8h): 1210 mg/m<sup>3</sup>, 500 ppm

ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

propane - CAS: 74-98-6

ACGIH - Notes: (D, EX) - Asphyxia

VLE short - 1000 ppm

xylene - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

butane - CAS: 106-97-8

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

and isobutane - CAS: 75-28-5

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

VLE short - 1000 ppm

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

---

## SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	Various	--	--

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

Odour:	Caracteristic of solvent	--	--
Odour threshold:	Unavaible	--	--
Melting point/freezing point:	Not relevant for the type of product	--	--
Boiling point or initial boiling point and boiling range:	Not relevant for the type of product	--	--
Flammability:	extremely flammable	--	--
Lower and upper explosion limit:	Not relevant	--	--
Flash point:	Inf. 0 ° C	--	--
Auto-ignition temperature:	It is not self-igniting	--	--
Decomposition temperature:	Not relevant for the type of product	--	--
pH:	8	--	--
Kinematic viscosity:	Not relevant for the type of product	--	--
Solubility in water:	NO	--	--
Solubility in oil:	Yes	--	--
Partition coefficient n-octanol/water (log value):	Not relevant for the type of product	--	--
Vapour pressure:	20°C - 5,0 bar 50°C - 8,0 bar	--	--
Density and/or relative density:	0,75 - 0,80 g/ml	--	--
Relative vapour density:	Not relevant for the type of product	--	--

Particle characteristics:

Particle size:	From 11 to 80 micron	--	--
----------------	----------------------	----	----

9.2. Other information

Properties	Value	Method:	Notes:
Explosive properties:	Section 10.3	--	--

## SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

- can form explosive vapour/air mixtures in poorly ventilated places
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products  
None.

---

#### SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

VERNICE PER CALORIFERI SPRAY

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

acetone; propan-2-one; propanone - CAS: 67-64-1

LD50 (RABBIT) ORAL: 5300 MG/KG

xylene - CAS: 1330-20-7

LD50 (RAT) ORAL: 5000 MG/KG

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

---

#### SECTION 12: Ecological information

- 12.1. Toxicity  
Adopt good working practices, so that the product is not released into the environment.  
VERNICE PER CALORIFERI SPRAY  
Not classified for environmental hazards  
Based on available data, the classification criteria are not met
- 12.2. Persistence and degradability  
None  
N.A.
- 12.3. Bioaccumulative potential  
N.A.
- 12.4. Mobility in soil  
N.A.
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties  
No endocrine disruptor substances present in concentration  $\geq 0.1\%$
- 12.7. Other adverse effects  
None

---

#### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information

- 14.1. UN number or ID number  
Not classified as dangerous in the meaning of transport regulations.  
ADR-UN number: 1950  
IATA-Un number: 1950  
IMDG-Un number: 1950
- 14.2. UN proper shipping name  
ADR-Shipping Name: AEROSOL  
IATA-Shipping Name: AEROSOL  
IMDG-Shipping Name: AEROSOL  
N.A.
- 14.3. Transport hazard class(es)  
ADR-Class: 2.5F  
IATA-Class: 2.1  
IATA-Label: 2.1  
IMDG-Class: 2  
N.A.
- 14.4. Packing group  
ADR-Packing Group: -  
IATA-Packing group: -  
IMDG-Packing group: -  
N.A.
- 14.5. Environmental hazards  
Marine pollutant: Marine pollutant  
N.A.
- 14.6. Special precautions for user



## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

IATA-Passenger Aircraft: ---  
IATA-Cargo Aircraft: 203  
IMDG-Shipping Name: AEROSOL  
N.A.

14.7. Maritime transport in bulk according to IMO instruments  
N.A.

---

#### SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) n. 2020/878  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Regulation (EU) n. 2016/918 (ATP 8 CLP)  
Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
Regulation (EU) n. 2017/776 (ATP 10 CLP)  
Regulation (EU) n. 2018/669 (ATP 11 CLP)  
Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
Regulation (EU) n. 2019/521 (ATP 12 CLP)  
Regulation (EU) n. 2020/217 (ATP 14 CLP)  
Regulation (EU) n. 2020/1182 (ATP 15 CLP)  
Regulation (EU) n. 2021/643 (ATP 16 CLP)  
Regulation (EU) n. 2021/849 (ATP 17 CLP)  
Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3  
Restriction 40

Restrictions related to the substances contained:

Restriction 75

Volatile Organic compounds - VOCs = 582.60 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)  
Regulation (EC) nr 648/2004 (detergents).  
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1  
Product belongs to category: P3a

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

#### SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press Gas (Liq.)	2.5/L	Gases under pressure (Liquefied gas)
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

## Safety Data Sheet

### VERNICE PER CALORIFERI SPRAY

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.